



EoL

END OF LINE

2219 AUTOMATIC IN-LINE L-SEALER



Versatile units capable of wrapping up to 50 pieces per minute

Texwrap’s standard line of sealers are designed for L-seal applications where speed and rugged reliability are prime considerations. Built to the same exacting standards as our high speed wrappers, these versatile units are capable of wrapping up to 50 pieces per minute when combined with the proper infeed.

The 2219 is easy to use and rugged enough for constant operation. It comes standard with premium features not available on competitive models in this price range including low-mount film cradle, swivel operator panel, touchscreen library to easily recall package setups, and automatic dwell time compensator. The 100 FPM conveyor speeds and Texwrap’s exclusive Motion Trim™ technology make these units the fastest L-sealers on the market today. Allen-Bradley controls, restricted service-level menus, and AC VFD drives make the 2219 as popular with maintenance staffs as with operators.

When your application calls for an L-seal wrapper capable of continuous operation, Texwrap’s 2219 offers the lowest total-cost-in-operation available today.

FEATURES AND BENEFITS

- Swing arm control panel for easy operator access
- Low profile “lay-on” cradle with power film unwind now comes standard
- Enhanced guarding standard
- “Smooth Mate” contoured exit conveyor for smooth transfer of products
- Variable speed conveyors (20-100 FPM)
- Automatic dwell time compensator
- Password protected user levels Product library
- Thermostatically controlled hot knife seal system provides efficient long term operation
- Front or rear product edge trip
- Tubular steel construction with powder coat finish
- Multi-packing option creates single lane unitizing into one package

TYPICAL PRODUCT SPECIFICATIONS

Maximum Package Size	19"L x 15.5"W x 7"H (maximum dimensions cannot be combined)
Minimum Package Size	4"L x 2-3/4"W (standard) 2"L x 2-3/4"W (with closing conveyor)
Film Width	Maximum: 28" Centerfolded/Minimum 6" CF Optional: 54" flat unwind. 3322 optional 32" centerfold unwind
Electrical Requirements	240 Vac, 1 phase

Conveyor Height	Adjustable from 29.5" to 36"
Air Requirements	80 PSI, 4 CFM
Machine Controls	Allen Bradley
Maximum Package Per Min	Up to 50 packages per minute (speeds based on packaging size, configuration and optional features)

CONFIGURATION

Top View

