



“Speed, Flexibility, Dependable Performance”

STB-145LS | Servo Bottom-Lap-Seal Wrapper

Small footprint, Low maintenance, High speed

- Electronic servo head
- Economical
- Easy-to-operate
- Efficient
- Evolutionary



The 145LS is Texwrap's latest design advance for applications requiring the high speed wrapping of packages where a bottom lap seal is desired.


The 145LS retains all the hallmarks of design and proven reliability that the market has come to expect from Texwrap - all in a brand new compact size. Texwrap's patented orbital servo head combined with the 200 feet per minute conveyor speed make it the fastest and most flexible wrapper of its kind.

Even the film carriage has been designed with maximum production in mind. The spare-roll capacity, the ability to handle double length rolls, and the optional splicing device all mean more production with fewer film changes. Simplicity and ease-of-use were paramount in the 145LS design. The controls are easily accessible and intuitive to use. When combined with the color touchscreen controls on the swivel panel, the easy access sliding doors, and the quick-change film plow system, the 145LS gives new meaning to the term "operator-friendly".

From true Generation 3 servo design to solid 24/7 construction, the Texwrap 145LS provides the ultimate in reliability, ease of use, and minimum maintenance requirements resulting in the lowest total cost of ownership available on the market today.

Made in USA

Distributed by:



TEXWRAP[®]
525 Vossbrink Drive · Washington, MO 63090
Ph (636)239-7424 · Fax (636) 239-7322
sales@texwrap.com · www.texwrap.com

Features:

- Laser-cut, heavy-steel frame construction with durable powder-coated finish
- Maximum film/belt speed 200 FPM
- Patented orbital servo head design keeps blade & pad vertical through entire range of motion making tighter packages and reducing film usage.
- Heated bottom seal pad
- Swivel, color-touchscreen operator panel with diagnostics for machine troubleshooting
- Variable-speed, inverter-duty AC motors
- Overhead, powered-nip-roller film delivery system; maximum 40"W flat film
- Powered film cradle available for double put up rolls and high speed operation
- Variable speed, servo-controlled exit conveyor to relax bridged film at cross seal
- Dual-roll staging included
- Optional film splicing available
- Motorized seal height adjusted through touch-screen (optional)
- Automatic empty bag detection and rejection (optional)
- Multiple seal options: static, thermal, combinations, etc.
- ANSI-compliant interlocked guarding package with easy-access sliding doors that lift out allowing total access for preventative maintenance

Specifications:

Conveyor Width:	14"W	Electrical:	240/208V, 40 Amp, 3 phase
Cross Seal Width:	16"W	Air Requirements:	80 PSI, 1 CFM
Film Width:	Maximum 40" flat film	Conveyor Height:	Adjustable from 33" to 38"
Minimum Pkg Size:	4"L x 2"W	Control Panel:	Easy-access swivel-mounted
Maximum Pkg Size:	Infinite length x 14"W x 5"H	Maximum PPM:	Up to 250 PPM (dependent on application)
Footprint:	79 3/4"L x 63"W x 96"H		

